



## Fully Automatic World-Wide Universal Input Electronic Charger

Intelligent chargers follow battery impedance to end of charge cycle for all battery types. Fully automatic.

Red LED indicates AC POWER ON, yellow LED indicates battery is charging, green LED indicates float mode.

Aluminum case.

### World-Wide Universal AC Input 90 – 260 volts, 50/60Hz

- Charge control: modified constant current charge to a constant finishing voltage then to a float standby.
- Current Limiting.
- Fully automatic 3 stage charger can be left on the battery indefinitely.
- Can be used with any type lead acid battery, including conventional, maintenance free, deep cycle, gelled-type, valve regulated batteries.
- Finishing voltage: 2.28 volts per cell float; 2.4 volts per cell finishing. May be preset to customers specification for battery type.
- Full load at 2.1 volts per cell **continuous - 100% duty cycle**.
- Short circuit proof.
- Reverse polarity (5 amp models)

<b>JAC0512</b>	<b>5 AMPS</b>	<b>12 VOLTS</b>	<b>6.5 x 3.5 x 1.8</b>	<b>1.8 lbs.</b>
<b>JAC1212</b>	<b>12 AMPS</b>	<b>12 VOLTS</b>	<b>6.5 x 3.5 x 1.8</b>	<b>1.8 lbs.</b>
<b>JAC0224</b>	<b>2 AMPS</b>	<b>24 VOLTS</b>	<b>4.6 x 2.3 x 1.4</b>	<b>1.2 lbs.</b>
<b>JAC0524</b>	<b>5 AMPS</b>	<b>24 VOLTS</b>	<b>6.5 x 3.5 x 1.8</b>	<b>1.8 lbs.</b>
<b>JAC0724</b>	<b>7 AMPS</b>	<b>24 VOLTS</b>	<b>6.5 x 3.5 x 1.8</b>	<b>1.8 lbs.</b>

DC cordsets 3' long with ring terminals.

*NOTE: Chargers available for other currents and voltages, contact factory.*